

Apple Mac Pro 2013



Technical Specs

Performance	
Processor	3.5 GHz Intel Xeon E5 Six-Core 12MB L3 cache
Memory	16GB of 1866 MHz DDR3 RAM Standard / 64GB Max
Graphics	2 x AMD FirePro D500 with 3GB of GDDR5 discrete memory

Storage	
Storage (SSD)	256GB PCIe-based flash storage
Optical Drive	None

Input/Output Connectors	
Ports	6 x Thunderbolt 2 4 x USB 3.0
Display	1 x HDMI 1.4 6 x mini DisplayPort (via Thunderbolt 2 ports) Connect up to three 4K displays or six Thunderbolt displays
Audio	1 x Combined optical digital audio output/analog line out minijack 1 x Headphone minijack with headset output 1 x HDMI port supports multichannel audio output 1 x Built-in speaker

Connectivity	
Ethernet	2 x 10/100/1000 Mbps Gigabit Ethernet RJ-45
Wi-Fi & Bluetooth	802.11ac (802.11a/b/g/n compatible) / Bluetooth 4.0

General	
Power Requirements	Line Voltage: 100-120V AC or 200-240V AC (wide-range power supply input voltage) Frequency: 50 Hz to 60 Hz single phase Maximum continuous power: 450W
Environment Requirements	Operating Temperature: 50° to 95%deg;F / 10° to 35%deg;C Storage Temperature: -40%deg; to 116° F / -40° to 47%deg;C Relative Humidity: 5% to 95% noncondensing Maximum Operating Altitude: 16,400 feet / 5,000 m Typical Acoustical Performance, Sound Pressure Level (Operator Position): 12 dBA at idle
Dimensions & Weight	9.9 x 6.6" / 25.1 x 16.7 cm 11lbs / 5kg